

## 1.8M Flyaway Antenna

- 1) 0.55/0.75/1.0/1.2/1.8m
- 2) Material is mainly carbon fiber
- 3) C-band and KU-band are available
- 4) Two air check box packaging

1.8M Ku Band Offset-feed Aantenna		
Gain	Tx	39. 5 dBi
	Rx	35. 5dBi
Operation frequency	Tx	5. 85–6. 65GHz
	Rx	3. 4–4. 26GHz
Slewing area	elevation	5—90°
	azimuth	360°
	polarization	±90°
Polarization	Linear	
Humidity operational	≤95%(30° C)	
Wind load operational	11m/s	
Temperature operational	-45—60° C	
1.8M Ku Band Offset-feed Aantenna		
Specifications	Ku-Receive	Ku-Transmit
Frequency(GHz)	12. 25–12. 75	14. 0–14. 5
Typical Gain(d B)	45. 44	46. 37
Beam width: -3dB	0. 878°	0. 789°
Feed Insertion Loss(d B)	0. 25dB	0. 25dB
VSWR	1. 25:1	1. 25:1
Tx-Rx Isolation	85dB	
Side Lobes	CCIR. 508-4	Side Lobes
Feed Insertion	WR-75	
Cross Polarization Isolation	Axis	≥35dB
	1dB Beam width	≥33dB
Power Handing Capability	1KW/Port	
Surface Accuracy (R. M. S)	0. 3mm	
Ambient Temperature	-30° ~ +60°	
Survival Wind Speed	125mi/h (200Km/h)	
Elevation travel	5° ~85°	
Azimuth Travel	0° ~360°	
Operational Wind Speed	45mi/h (72Km/h) gusts to 60mi/h (97Km/h)	
Relative Humidity	0%~100%	